

SYRINGE PUMP PORTABLE

XB-500

EPOWER ELECTRONICS & SCIENCE CO.,LTD

3/F,BUILDING5,NANSHAN YUNGU INNOVATION INDUSTRIAL PARK
SHENZHEN 518055, P.R.CHINA SHENZHEN, CHINA

Phone: 86-755-86008946 Email: phoebe.wang@epowerchina.com
http://www.hospytek.com/epower-electronics-science-co-ltd



OVERVIEW:

DESCRIPTION:

Minimum Syringe: 1ml Syringes Injector: 5 User-defined
Injectors Syringe Accuracy: Continuous Injection Less Than
 $\pm 2\%$ Weight: 180g Alarm Type: Sound, Light, Shake Brand Name:
Epower

TECHNICAL SPECIFICATIONS:

Applicable syringe: 1ml, 2.5ml, 5ml, 10ml, 20ml (30ml) disposable syringes Linear
Flow Rate: 0.1ml/hr – 99.9ml/hr 3, Flow Rate: 1ml syringe:
0.1- 10.9ml/hr, 2.5ml syringe:
0.1-36ml/hr, 5ml syringe: 0.1- 66ml/hr, 10ml syringe:
0.1-99.9ml/hr, 20ml syringe: 0.1-99.9ml/hr..

[READ MORE](#)